BIKE SPECIFICATIONS

DETAILS	IC5	IC6	IC7
POWER MEASUREMENT (WATT)	WattRate® Power Meter (EN ISO 20957-10)	WattRate® Power Meter (EN ISO 20957-10)	WattRate® Direct Power Meter (+/-1%)
COMPUTER	WattRate® LCD Computer	WattRate® TFT Computer	WattRate® TFT Computer
COMPUTER POWER SUPPLY	Self-powered generator with capicitor	Self-powered generator with LiPo battery	Self-powered generator with LiPo battery
TRAINING INTENSITY GUIDE	Coach By Color® (user & instructor)	Coach By Color® (user & instructor)	Coach By Color® (user & instructor)
CONNECT TECHNOLOGY	Bluetooth and ANT+	Bluetooth and ANT+	Bluetooth and ANT+
WORKOUT TRACKING	ICG® Training App and Apple Watch	ICG® Training App and Apple Watch	ICG® Training App and Apple Watch
WORKOUT DATA TRANSFER	Strava, Garmin via ICG® Training App	Strava, Garmin via ICG® Training App	Strava, Garmin via ICG® Training App
THIRD PARTY APP CONNECTIVITY	Zwift	Zwift	Zwift
RESISTANCE SYSTEM	Magnetic	Magnetic	Magnetic
EMERGENCY STOP	Push (EN ISO 20957-10)	Push (EN ISO 20957-10)	Push (EN ISO 20957-10)
FLYWHEEL	Rear, aluminum, evenly-weighted	Rear, aluminum, evenly-weighted	Rear, aluminum, evenly-weighted
DRIVETRAIN	Poly-V belt	Poly-V belt	2-Stage Hybrid Poly-V & tooth belt
DRIVETRAIN GEAR RATIO			1:11
FRAME COLOR	Charcoal black	Charcoal black	Charcoal black
FRAME MATERIAL	Steel	Steel	Steel
SHROUDS/GUARDS	Full frame	Full frame	Full frame
FRAME DESIGN	Off-set	Off-set	Off-set
ADJUSTMENT TYPE	Dials & levers	Dials & levers	Levers
POSTS & SLIDERS	Black Aluminum, pin-to-lock adjustment	Black Aluminum, pin-to-lock adjustment	Black anodized Aluminum, stepless adjustment
USER ASSIST ADJUSTMENTS	Handlebar assisted	Handlebar assisted	Handlebar and saddle assisted
Q FACTOR			155mm / 6.1"
CRANK TYPE	CrMo 172,5mm / 6.79"	CrMo 172,5mm / 6.79"	CrMo 172,5mm / 6.79"
PEDAL TYPE	Dual-sided SPD & toe cage	Dual-sided SPD & toe cage	Dual-sided SPD & toe cage
HANDLEBAR	Ergo-formed, Sprint-Pro, soft PVC	Ergo-formed, Sprint-Pro, soft PVC	Ergo-formed, Sprint-Pro, soft PVC
HANDLEBAR ADJUSTMENTS	Vertical & horizontal		Vertical & horizontal
SADDLE	Unisex padded sport saddle	Unisex padded sport saddle	Unisex padded sport saddle
SADDLE ADJUSTMENTS	Vertical & horizontal	Vertical & horizontal	Vertical & horizontal
WATER BOTTLE HOLDER	Dual, integrated on handlebar	Dual, integrated on handlebar	Dual, integrated on handlebar
FRAME STABILIZER BARS	Standard	Standard	Oversized, hidden bolts & fixings
PROTECTION & STRETCH PLATES	Molded form-fit with stretch plate	Molded form-fit with stretch plate	Molded form-fit with stretch plate
MAX USER WEIGHT	150 kg / 330 lbs	150 kg / 330 lbs	150 kg / 330 lbs
ASSEMBLED WEIGHT	51 kg / 112 lbs	51 kg / 112 lbs	54 kg / 119 lbs
ASSEMBLED DIMENSIONS	L132xW52xH102cm / 52"x20.5"x40.2"	L132xW52xH102cm / 52"x20.5"x40.2"	L132xW52xH102cm / 52"x20.5"x40.2"
LEVELING FEET	4	4	4
TRANSPORT	2 front wheels	2 front wheels	2 front wheels & rear lifting handle